

**DESCRIPTION:** PRIME SEAL is a water based acrylic concrete primer/sealer formulated to enhance and protect interior concrete and masonry surfaces. PRIME SEAL exhibits superior resistance to gasoline, chemicals, oils and grease.

---

**USES:** PRIME SEAL can be used:

- as a primer for BASALITE FLOORTOP®
- on interior concrete surfaces:
  - garage floors
  - basement floors
  - interior "Foundation" walls.

---

**ADVANTAGES:** PRIME SEAL is a water based acrylic that requires only water for clean up and is ideally suited for interior applications.

---

**PROCEDURES:** All surfaces to be in contact with PRIME SEAL must be clean and entirely free of oil, grease or any other foreign substances which interfere with the bond and chemical action of the material. This can be achieved by scrubbing with a soap solution of trisodium phosphate (TSP), a mild acid solution, or power washing. After cleaning, rinse the surface thoroughly and let dry. Shake PRIME SEAL well before use and apply uniformly without puddling by spray, brush or roller to the dry surface. Apply at temperatures above 10°C (50 °F).

---

**CLEAN -UP:** Tools and equipment can be cleaned up with water.

---

<b>TECHNICAL DATA:</b>	Appearance:	Milky white liquid
	Density (25 deg C):	1.0009 kg/litre (10 lbs/gallon)
	Dry Film Appearance:	Clear
	Coverage:	9 to 18 m <sup>2</sup> (100 - 200 sq.ft.) per litre
	Drying Time:	1 hour

---

**LIMITATIONS:** PRIME SEAL is designed to be used as supplied; do not alter or dilute the product. Do not allow PRIME SEAL to freeze. Liability for damages or defective goods shall be limited to the refund of the purchase price or product replacement.

---

**PACKAGING:** PRIME SEAL is packaged in 1 litre and 4 litre containers.

---

**SAFETY PRECAUTIONS:** Normal safety such as rubber gloves, dust masks and safety glasses are recommended. Avoid prolonged contact with skin. Keep out of reach of children. Material Safety Data Sheets are available upon request.